KOOTENAI JOINT SCHOOL DISTRICT #274° HARRISON ELEMENTARY SCHOOL APRIL 1992

Trustees:

SHAWN FLY, CHAIRMAN

DICK BLAKLEY, VICE-CHAIRMAN

JEAN DOHRMAN

DONNA LAYTON

LES THOMAS

RON HILL, E ERINTENDENT

JIM BELLAMY, ARCHITECT

ERIC R. BROWN CONSTRUCTION, CONTRACTOR

KOOTENAI JOINT SCHOOL DISTRICT #274 MULTIPURPOSE ROOM APRIL 1990

Trustees:

Shawn Fly, Chairman
Dick Blakley, Vice-Chairman
Rick Harlow
Jean Dohrman
Howard ilson

Ron Hill, Superintendent

Jerry Ressa, Architect, Pacific Design

Eric R. Brown Construction, Contractor



March 22, 2016

Kootenai School District Bob Dionne – Maintenance Supervisor 13030 E. O'Gara Road Harrison, ID 83833

RE: Kootenai Elementary School and Multi-Purpose Building

Dear Mr. Dionne-

Approximately 20 to 25 years ago my previous company, Eric R. Brown Construction, built both the Kootenai Elementary school and Multi-Purpose building. To the best of my knowledge no lead based solder containing materials were used in the construction of either structure. At that time lead based solder was not allowed in construction products.

Sincerely,

Eric Brown

President - Brown Contracting and Development, Inc.

CERTIFICATION OF SAMPLING SITES						
LEAD SOLDER SITES (Enter only count of sites from which samples were actually drawn)						
# of residences with lead pipes or copper pipes & lead solder \times installed after December 31, 1982 (Tier 1). # of non-residential buildings containing lead pipes or copper pipes & lead solder \times installed after December 31, 1982 (Tier 2) to be used only if Tier 1 has been exhausted). # of sites that contain copper pipes & lead solder installed before 1983. (Tier 3; to be used only if tiers 1 & 2 have been exhausted.) **TOTAL** **Solder in plumbing installed before June 19, 1988 will automatically be assumed to contain lead. Solder in plumbing installed after the federal lead ban which began in Idaho on June 19, 1988 will need to use the scraping test described below before it can be used to satisfy lead solder criteria.						
The following sources have been explored to determine the number of structures which have interior lead pipe or copper pipe with lead solder:						
Analysis of filings scraped from solder joints. (Field analysis kit is sufficient.) Plumbing or building codes Plumbing or building permits Contacts within the building department, municipal clerk's office, or state regulatory agencies for historical documentation of the service area development. Water Quality Data Interviews with building inspectors Survey of service area plumbers about when & where lead solder was used from Jan. 1, 1983 to present. Survey of residents in sections of the service area where lead pipe and/or copper pipe with lead solder is suspected to exist Interviews with contractors and developers						
Explanation of Tier 2 & tier 3 sites (Attach additional pages if necessary.) All. pres Installed in 1953 (galvinged pipe was used) LEAD SERVICE LINE SITES (Should comprise 50% of total samples collected.)						
# LSL samples required # LSL samples taken Difference (explain if unequal to zero)						
Explanation of difference (attach additional pages if necessary):						
The following sources have been explored to determine the number of lead service lines in the distribution system.						
Distribution system maps and record drawings Information collected for the presence of lead pipes and/or copper pipes with lead solder Capital improvement plans and/or master plans for distribution system development Current and historical standard operating procedures and/or operation & maintenance manuals for the type of materials used for service connections						

Utility records including meter installation records, customer complaint investigations and all historical documentation

MATERIALS SURVEY INVESTIGATION RESULTS

PWS ID Number

280107


Population Served

									BHG	Type of Structure Structure School 1953
										Year Built
						A STATE OF THE STA	 The state of the s			Location Harrison Flave
					· · · · · · · · · · · · · · · · · · ·			•	Korry Bear	Contact Person
									689-3311	Person LSL? Phun Phone Yes; No Ma
									140	LSL? Yes, No
									Calin 200	ome nbing teria
		-							Yes	

"Home plumbing material" column: Enter "Pb" if interior pipe is lead; "Pb/Cu" if copper with lead solder; or name any other m First Column "structure types": SFR = single family residence; MFR = multifamily residence; Bldg = other types of buildings "Volunteered" column: Enter "no" if customer refused to participate. "LSL" column: LSL = Lead service line; enter "yes" if pipe between the house and the water main is made from lead, otherwis

Last column, "training material": Make entry only if site actually was used for sampling.







March 22, 2016

RE: Copper Pipe Solder – Kootenai High School

To whom it may concern,

I have reviewed the mechanical construction specifications for the Kootenai High School located in Harrison, Idaho and find the solder type specified is 95/5 (no lead) solder. Shop drawings for the product intended for use are not available for review. Mechanical system design was by Riley Engineering, Inc. The review of these documents does not provide any guarantee of accuracy for actual product used for construction. Field sampling should be performed and tested for positive affirmation of the product used if desired.

Sincerely,

Michael G. Hubbard, P.E., Principal

Riverside Engineering, PLLC.

N. 5770 Hauser Lake Road Post Falls, Idaho 83854 4-A

(208) 773-2563 1-800-634-4914

GENERAL CONTRACTOR • LICENSED • BONDED • INSURED for your protection COOKSI 15CDF

Sales Contract and Work Order

I/we the owner(s) of the premises mentioned below hereby authoworkmanship, to install, construct and place the improvements a	rize you as contractor, to according to the followi	to furnish all n ing specificatio	ecessary mai ns, terms ar	terials, labor, and and conditions, on	
premises below described:					
Contractor will build a steel covered building over-all measurements				long	
Wall height of main body to eave	Roof Pitch	/ }			
Shed Roof: Front Height	Rear Height	t	<u> </u>		
Shed Roof: Front, Height Insulation: Type 3" R-1/ Shed Roof: Type	Location _ (! D /)	pleta			
Feeders: Width Length	Eave Height	Lo	ocation		
Mangers	Location				
Enclosed Shop Size	Location				
Open Bays	Location				
Reducator C. o / galvanized steel	29	Gauge			
Roof color (1 () / galvanized steel	<u> </u>	Gauge		21	100
Steel covered doors color	Trim color	De	luxe	<u>e</u>	
Roof color	in ground with con-	crete. With 4 x	3 pressuré tre	eated stub posts or	
- walk in door hanners. Fir framing lumber-stangard and better, with a	iiio Eniliiie abbiovi z ieer	CONTROL DOG	DIO 11400 DQ	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Bolt Size // Rafters		_Cross Ties		vvebbing	
Courses 2 x/6 T and G-pressure treated around base of bu	ilding	(c) Dra	wing		
Atuminum windows: sizes 9X3		Location	(c)	Drawing	-
Solid Core Walk-in Door — Left Hinge_	Right Hinge	Location	(c)	Drawing	
NOTE: The maximum height of a sidewall sliding door is one foot le	ss than eave height.				
2 Cliding Dance: sizes and clearance / D X / R		Location	(c)	Drawing	
Sliding Doors (Split) sizes and clearance		Location)(C)	Drawing	
Overhead Doors: sizes Tilt U	Jp Roll Up	Location_	(c)	Drawing	
5 Inches thick concrete slah: Location: Wire	Finish Rough		Smooth		
Owner to prepare site	Company to prepare sit	te	FIII If Required	d will be	
Owner to prepare site Cont Permit: Owner_	Cont. L		supplied by	75000012	er Ar defension of the
Clean op. Omloi		V: A	·		A Mornet
	Cb Drine	gut 18	231	040 1	27/5/
(CASH JOBS)	Cash Price	50° (v_	1.70× 0	7	Laul
50% or more must be paid down on cash jobs. Payment must	Tax	18	4.4.		Mark Addition
he made at time of contract. Balance of contract price must be	Sub total	<u>Ψ</u>			Contract the second
paid on the date of completion or interest at the rate of 1% per month will be charged from date of completion to date of		Ş			Name of the second second
payment.	<u></u>	\$			•
£.,	Down Payment	-		į.	•
GIVE FINAL BUILDING PAYMENT TO	Unpaid Balance			i	-
FOREMAN ON COMPLETION	Time Payment Charge				
1 Alleman An Aam Penan	Total	\$			-

BUILDING PERMIT APPLICATION

Jurisdiction of Kootenai County, Idaho

Permit H18402

		23 WAFFED LI					
JOB ADDRESS	<i>c.</i>	2 SECTION TOWNSHIP RANGE					
PARCEL NUMBER	77.5	4 SERIAL NUMBER 34 1914					
LEGAL DESCR.	E 40.01119	(SEE ATTACHED SHEET					
OWNER	7 CONTRACTOR	R Alexander					
1 11 274							
Live Boy 25 HARRIS	ora f						
258	132 / April	e 627 2631					
ARCHITECT OR DESIGNER	9 ENGINEER						
0 Class of work: DNEW DADDITION DAL	TERATION D SETTING PE	ERMIT OTHER CODE					
11 DESCRIBE WORK 12 DIRECTIONS							
- 12 10 E/E 18 MO BA: 1 C ARA	by 3 //e.	13 10 14 wy 4 2					
3 SPECIAL CONDITIONS SIZE	Valuation of wor	k PERMIT FEE \$					
	PLAN CHECK F	EE TOTAL FEE					
	Type of Const.	Occupancy Division					
APPROVE APPROVE APPROVE		No. of Max. Occ. Load					
ACCEPTED BY CHECKED BY ISSUANCE	14 6/110 006	14 LAND USE - CHECK: IND COM RES M.H. COTHER C					
NOTICE	15 ZONING						
Separate permits are required for electrical, plumbing, heating, ventilating or tioning. This permit becomes null and void if work or construction authorized is not or within 180 days, or if construction or work is suspended or abandoned for pedays at any time after work is commenced.	ommenced 16 HIGHWAY D	1 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0					

Kootenai Jt. School District #274

5-4

Superintendent, Scott Davis Principal, Nolan Kerby Business Manager, Stacia Dorman DISTRICT OFFICE 13030 E. O'Gara Road Harrison, ID 83833-7641 Phone: 208-689-3631 Fax: 208-689-3641

- 1. Snack Shack: Built 2007 Visual Confirmation -Plastic
- 2. Bleacher Stand: Pipe: Visual Confirmation -Galvanized-Plastic
- 3. Log House: Stand Pipe Visual Confirmation-Galvanized -Plastic
- 4. Football Field Irrigation: Visual Confirmation- Galvanized

Robert Dionne Maintenance Supervisor To Whom it may concern,

I can state that the underground water line from the well house to what is now the Jr. High, what used to be the High School for Kootenai Jt. School District #274 Harrison, ID is 4" galvanized steel.

Sincerely,

and was expensed water brakes in the lene to the select

Duane Thompson

Maintenance Supervisor 1971-1977

4-18-2023

To Knotenan High School

Bob Disnove, (Maintonere)

(water have From well house to thish Bobol)

On 4-18-2023 Bob call Me about the water Line at Koofena High Glood, From the well brouse to the old thigh School (Now Journer High) I worked for the Kootena With School From 1977 to the Mild 80 s as Head of Massila During my trace as Macintonel person I projects at the Districe, Ditch claims Ditch Dissing the water the was exposed, It is a 4" galvized Love from well House for barement Water Tank.

Kerry Beare

Lead and Copper Rule (LCRR)

The EPA published the LCRR on January 15, 2021, and formally approved it in December 2021. The revisions improve the Lead and Copper Rule to eliminate lead contamination in drinking water and increase public health protection by reducing lead exposure.

These revisions apply to 40 CFR Parts 141 and 142. At this time, the State of Idaho is following the EPA Guidelines (please refer to 40 CFR § 141.84 Lead service line inventory requirements) and the initial compliance deadline is October 16, 2024.

Lead and Copper Rule Improvements (LCRI)

It is important to note that we are exploring the rule as it is written in the law today. Still, the EPA has expressly committed to improving the regulation on a few key fronts and plans to promulgate the "Lead and Copper Rule Improvements" (LCRI) before the compliance deadline. On August 4th, 2022, the EPA released its final update to the "Inventory" component of the law and stated further that they would evaluate the other components. It is essential to know that the Inventory is final and will not change. Although the EPA issued Lead and Copper Rule Revisions (LCRR) in January 2021, the agency did not address practices for lead pipe replacement. The EPA later reviewed the LCRR to determine if it adequately protected families and communities, especially those at risk from lead in drinking water. The agency concluded that significant opportunities existed to improve the LCRR and proposed

the LCRI.

Improvements include four priorities:

- 1. Replace lead service lines proactively and equitably.
- 2. Improve compliance with sampling at the tap to identify communities most at risk of lead in drinking water and compel action to reduce lead.
- 3. Decrease the complexity of the regulation (i.e., trigger-level vs. action-level, sampling methods, replacement schedules, etc.)
- 4. As part of the LCRI rulemaking process, the EPA is considering prioritizing protections for historically underserved and overburdened communities.

The Safe Drinking Water Act also requires the EPA to consult with the SAB on tools, indicators, and measures to evaluate the environmental justice impacts of lead service line presence and replacement in drinking water systems.



HISTORICAL CONTEXT

LCR BEGINNINGS

To know where we're going, it's important to know where the regulation began, how we've changed, and how not to repeat ourselves. Knowing the timeline helps explain WHY the changes are happening, which is ultimately for every community to have zero lead and copper in your system. While that may feel impossible now, this timeline represents how much closer we are to achieving that goal.



PRO TIP

Use this timeline to brief your staff, elected officials, the general public, schools, and media.

Federal Lead Pipe Timeline

If you live in a home built before 1986, it's possible there are lead pipes in your system. No matter the piping material, you will have to account for lines via an inventory – for which many utilities lack reliable or complete data.

Here's a quick rundown of our early days:

- 1800s Installation on a major scale
- 1930 Some cities moving away from LSL use
- 1970 LIA Campaigns End
- 1977 Changes to plumbing codes
- 1986 Federal LSL ban (Date of Lead Ban in each State Varies from 1986 - 1991)

DATE	ACTION	RESULT
1974	The Safe Drinking Water Act (SDWA) was passed to protect our drinking water. The US Environmental Protection Agency (EPA) sets the standards for drinking water quality and monitors states, local authorities and water suppliers who enforce those standards.	The EPA sets legal limits for more than 90 contaminants in drinking water, including chemical and microbial contaminants.
1986	Congress amended the SDWA prohibiting the use of pipes, solder or flux that were not "lead free" in public water systems or plumbing in facilities providing water for human consumption.	At the time "lead free" was defined as solder and flux with no more than 0.2% lead and pipes with no more than 8%.
1991	EPA first issued the Lead and Copper Rule (LCR) to limit concentrations of lead and copper in public drinking water.	The rule also set a standard for pipe corrosion control, a proven method of controlling contaminants in drinking water.
1996	Congress further amended the SDWA requiring plumbing fittings and fixtures to be in compliance with voluntary lead leaching standards.	Further amended the SDWA to clarify that its "lead free" prohibition on the use of pipes, solder, and flux also applies to pipe fittings, plumbing fittings, and fixtures.



SCHOOL AND DAYCARE SAMPLING

No amount of lead is safe for children.

A recent study by the World Health Organization (WHO) found that when adults drink water with lead, they absorb up to 10%, but when children drink water with lead, they can absorb 40-60%. Consuming lead can cause nervous system damage, learning disabilities, behavioral problems, and in extreme cases, seizures, comas, and even death. Ever since the crisis in Flint, Michigan, lead in schools and facilities has been top of mind and a prevalent legislative issue. As of November 2021, almost half of the nation had voluntary programs in place and 18 states currently had mandatory programs. This has been the trend with the U.S. clearly prioritizing lead removal where children are present.



Water systems can get a head start for sampling schools and childcare facilities. Here are a few ner ommendations

- Build a list of the schools and all licensed childcare facilities in your service area
- Meet with stakeholders to bring awareness of upcoming changes
- Provide training and education

REASON YOUR INVENTORY IS THE FOUNDATION

FOR LCRR

SCHOOL AND DAYCARE SAMPLING, continued

Before LCRR, lead sampling in school facilities was the responsibility of states, cities, and individual facilities. With the updated regulation, school and daycare sampling will now fall to water systems to operate, including the following:

IDENTIFY

Every water system will be required to create an inventory of facilities they serve – elementary schools, middle schools, high schools, preschools, daycares, etc.



Utilities must sample 20% of elementary schools and 20% of all childcare facilities in the service area each year for five years

- Five (5) samples per school and two (2) samples per childcare facility
 - Schools Sample:
 - Two (2) drinking water fountains,
 - One (1) kitchen faucet used for food or drink preparation
 - One (1) classroom faucet or other outlet used for drinking
 - One (1) nurse's office faucet (as available)
 - Child care facilities Sample:
 - One (1) drinking water fountain
 - One (1) of either a kitchen faucet used for the preparation of food or drink OR one (1) classroom faucet or other outlet used for drinking
- · Secondary school sampling must also be provided when requested.



You must deliver results and public education to each sampled facility, primary agency, and health department.